

**GRAPHICS** - INK-JET DIGITAL

Issue date : 11/11/2015 Date last modification : 12/04/2018

# 4-GL3B-08461 RI-JET 75 OPTIMA GLOSS WHITE AP940 PERMANENT GREY WKPE140 AIRFLOW N

# Face Material

Gloss white polymeric soft vinyl.

Type Colour and Finish Weight Thickness 
 Polymeric vinyl

 Gloss white

 100 g/m² ±10%
 ISO-536

 75 μ ±10%
 ISO 534-80

# Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference
Туре
Min. Appl. Temp.
Service Temp.
Shear
Tack
Final Adhesion

AP940 permanent GREY Acrylic permanent +10°C -30°C/+120°C Very High 6 N/25mm FINAT FTM9 11 N/25mm FINAT FTM2

#### Liner

Туре	Embossed PE coated kraft paper - Airflow texture	
Colour and Finish	White	
Weight	140 g/m² ±10%	PP-032 - ISO
C C	<b>C</b>	536
Thickness	150 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

# **Applications**

For advertising and promotional applications (window graphics, outdoor and indoor posters, billboards and signs) and for vehicle applications (for flat sided including buses, trams and taxis and for corrugated surfaces and vehicle wrapping).

# **Printing Methods**

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

# Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of  $~22^\circ\text{C}$   $\pm~2^\circ\text{C}$  and 50  $\pm~5\%$  of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



Ritrama S.p.A. Via Senatore Simonetta, 24 20867 Caponago (MB) ITALY e-mail:info@ritrama.com w w w . r i t r a m a . c o m

