

Technical Data Sheet

Issue date: 30/09/2015 Date last modification: 12/04/2018

GRAPHICS - INK-JET DIGITAL

4-GL3C-08459 RI-JET 75 OPTIMA GREYOUT GLOSS WHITE AP940 PERMANENT **GREY WK135 N**

Face Material

Gloss white polymeric vinyl.

Polymeric vinyl Type Colour and Finish Gloss white

100 g/m² ±10% ISO-536 Weight ISO 534-80 **Thickness** 75 µ ±10%

Adhesive

Acrylic permanent adhesive with grey pigmentation featuring very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference AP940 permanent grey

Acrylic permanent Type

Min. Appl. Temp. +5°C -30°C/+120°C Service Temp.

Shear Medium Tack Medium N/inch² Final Adhesion High N/inch

<u>Liner</u>

Type One side siliconised clay coated

Kraft

Colour and Finish White

PP-032 - ISO Weight 135 g/m² 536

±10%

145 µ ±10% ISO 534 **Thickness** Transparency n.a. % DIN 53 147-64

Applications

Highly stable polymeric film that satisfies different application requirements in several sectors, such as medium-long term dynamic advertising, shop windows decorations and partial vehicles wrapping.

Printing Methods

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following STORAGE CONDITIONS:

- This material must be stored at a temperature of $22^{\circ}C \pm 2^{\circ}C$ and $50 \pm$ 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



